

~~Instrumented antifriction bearing and electrical motor equipped therewith~~

BACKGROUND OF THE INVENTION

1. Field of the Invention

~~_____The present invention generally relates to an antifriction bearing in which a rotating member of the bearing supports an encoder and a nonrotating member of the bearing supports a sensor that may be used to for the purpose of determining determine certain rotation parameters such as the speed or the angular position of the rotating element supporting the encoder. Such devices find their application in many fields. The present invention also relates to antifriction bearings for use in such as electric motors, in which they are required to operate in severe conditions of speed and temperature conditions.~~

2. Description of the Relevant Art

~~_____Through document French Patent No. 2,754,903FR-A-2 754 903, describes an antifriction bearing is known comprising that includes a sensor integral with on the nonrotating racetrack, of the Hall effect probe type, and an encoder integral with on the rotating race-track moving in rotation with a slight air gap relative to the sensor while being capable of producing in the sensor a periodic signal with a frequency proportional to the rotation speed of rotation of the rotating racetrack. The encoder comprises includes an annular active portion, made with The annular active portion includes a plastic magnet and provided with an active zone portion placed opposite the sensor. The active portion may be supplemented by a reinforcement portion consisting of that includes two annular elements placed in contact with the active portion, on either side of the active zone.~~

~~_____Such an This type of antifriction bearing is usually satisfactory, particularly in the field of electric motors. However, this type of encoder cannot operate at high temperatures, above 120°. In addition, The sensor and the encoder do not operate satisfactorily if they are subjected to high intensity external magnetic fields, for example the magnetic fields induced by the coils of the stator of electric motors and/or by the electromagnetic brake built into said the motors. Finally, the axial compactness of the this type of antifriction bearing thus instrumented is not optimal and does not make it is not easy to incorporate.~~

STRIKETHROUGH SHEET

5 | _____ In high power asynchronous electric motors, ~~the~~ control of the motor requires
detection of the rotation parameters of the motor ~~to be detected~~. Specifically there is a need to
know the Knowledge of speed and direction of rotation of the rotor may be needed to be able
to adapt the frequency, ~~the current~~ and the direction of the current entering the coils of the
stator. The use of a multipolar type encoder associated with a Hall effect probe is suitable
only for applications in which the power and the control requirements are relatively
imprecise, for example for a fan motor that operates at constant speed during use. ~~Also~~
known are the ~~Optical~~ type sensor encoder systems, such as ~~for example~~ industrial encoders,
10 | ~~which are not likely to be built into a motor, which~~ require a mechanical interface for driving
by the electric motor and ~~which~~ are relatively sensitive to impacts and to temperature.
Optical type sensor encoder systems are not likely to be built into a motor.

15 | _____ The invention aims to remedy these disadvantages.

STRIKETHROUGH SHEET

SUMMARY

~~The invention proposes~~Herein we describe an instrumented antifriction bearing that is
may be axially ~~very compact,~~ and ~~may capable of operating operate~~ at high temperatures
5 while delivering precise detection,~~;~~ ~~The antifriction bearing may also~~including when they are
subjected to intense magnetic fields.

~~In some embodiments, The instrumented antifriction bearing device, according to one~~
10 ~~aspect of the invention, comprises~~ may include a rotating portion, a nonrotating portion and
an assembly for detecting rotation parameters. An assembly for detecting rotation parameters
may include ~~comprising~~ an encoder and a sensor. A sensor may be integral-integrated with
the nonrotating portion and ~~provided~~ may include with a sensor unit. ~~A~~The sensor ~~comprises~~
15 may include at least one microcoil with a substantially flat winding. A microcoil may be
positioned, ~~placed~~ on a support of a circuit mounted in the sensor unit of the nonrotating
portion ~~such so that said the microcoil comes~~ may be axially opposite the encoder. This may
provides satisfactory axial compactness.

~~In one embodiment, the device comprises~~ may include a plurality of substantially
20 radial coplanar reception microcoils, which may allow. ~~The sensor may thus achieve~~
substantially precise detection. In ~~another certain embodiments of the invention,~~ the device
~~comprises~~ may include a plurality of reception microcoils ~~placed~~ positioned on a plurality of
parallel radial planes. ~~This provides a~~ An increased ~~greater~~ number of reception coils may
provide ~~providing~~ enhanced precision.

~~Advantageously, In some embodiments,~~ the device ~~comprises~~ may include a
25 transmission coil ~~placed~~ positioned in the sensor unit. The transmission coil may also be a
microcoil,~~;~~ preferably A microcoil may have with a flat winding. ~~Preferably, the~~ In an
embodiment, a device ~~comprises~~ may include at least one transmission coil, at least one
reception coil, and a data processing circuit ~~placed~~ positioned on the support. These elements
30 ~~can~~ may be used to retain a ~~satisfactory~~ desired axial compactness. The coils may be made ~~in~~
using printed circuit technology. The support may ~~be~~ include a printed circuit substrate in the
form of a resin circuit board. ~~In other words, the~~ A sensor comprises may include active

STRIKETHROUGH SHEET

and/or passive elements combined in a single module ~~integral-integrated~~ with the nonrotating portion.

5 ~~Advantageously~~In some embodiments, the device ~~may include~~ comprises a plurality of microcoils. Microcoils may be linked-coupled together in pairs and/or angularly offset in order to generate a differential signal. The encoder may ~~comprise-include~~ include an encoder wheel. An encoder wheel may include ~~whose-an~~ an active zone is made of an electrically conducting metal. In certain embodiments, Advantageously, the encoder ~~comprises-may include~~ may include a printed circuit with whose-substrate is-an ~~annular-in~~ shaped substrate ~~and is provided with that~~ includes metallized sectors and nonmetallized sectors. The printed circuit may be mounted on a nonrotating ~~raeetrack~~ track of the antifriction bearing.

15 ~~In another-some~~ embodiments of the invention, the encoder ~~comprises-may include~~ may include an encoder wheel with windows and/or with-teeth attached to a rotating ~~rae-track~~ track of the antifriction bearing. The encoder may be ~~made-as-a~~ substantially solid block. The encoder may be ~~made-of~~ pressed sheet metal. ~~Such-an~~ An encoder is ~~capable-of-may~~ operating-operate at high temperatures. For the purposes of this application, w~~Windows are here intended to mean-refer to~~ holes formed in the encoder between two circumferentially continuous portions. For the purposes of this application, T~~teeth are intended to mean-refer to~~ portions of material that are ~~integral-integrated~~ with a circumferentially continuous portion of the encoder. The encoder may ~~comprise-include~~ include an axial portion ~~fitted-onto-positioned on~~ a cylindrical bearing surface of the rotating ~~rae-track~~ track and a radial portion directed towards the other ~~rae-track~~ track and in which the windows or the teeth are formed.

25 ~~For reasons-of~~ To increase compactness, it is ~~advisable to ensure that~~ at least one portion of the encoder ~~may be positioned is-placed~~ is placed in the space situated between the antifriction bearing ~~raeetracks,~~ tracks, ~~that is to say~~ For example, a portion of the encoder may be positioned radially between the cylindrical surfaces of the ~~raees-tracks~~ tracks which extend between the bearing raceways and the frontal surfaces delimiting said ~~raeetracks;~~ tracks; and axially, at right angles to ~~said-the~~ the cylindrical surfaces, between the rolling elements and the frontal radial surfaces of the antifriction bearing ~~raeetracks.~~ tracks. ~~In another-certain~~ embodiments, -of the invention, the encoder is ~~placed-may be positioned~~ may be positioned outside the space situated between the antifriction bearing ~~raeetracks.~~ tracks.

STRIKETHROUGH SHEET

5 ~~_____ In one some embodiments, of the invention, the sensor unit is may be annular. In~~
~~another embodiment of the invention, the sensor unit may occupies an angular sector of less~~
~~than 360°, for example of the order of approximately 120°. In certain embodiments, In one~~
~~embodiment of the invention, the data processing circuit is may be an application-specific~~
~~integrated circuit (ASIC).~~

10 ~~_____ In some embodiments, The invention also proposes an electric motor may include~~
~~comprising a rotor, a stator, at least one antifriction bearing supporting the rotor, and a sensor~~
~~assembly comprising including an encoder and a sensor. The sensor comprises may include at~~
~~least one microcoil with a substantially flat winding placed positioned on a support of a~~
~~circuit that is mounted in the sensor unit integral and integrated with the stator such that the~~
~~microcoil comes is positioned axially opposite the encoder. Usually, the In an embodiment, a~~
~~winding will comprise may include an outer race track integral with the stator and supporting~~
15 ~~the sensor unit and an inner rotating race track integral with the rotor and supporting the~~
~~encoder. The motor may be of the high power asynchronous type in which precise control is~~
~~may be required and facilitated by measuring the rotation parameters precisely. For the~~
~~purposes of this application, a mMicrocoil here is intended to mean refers to a coil with a~~
~~winding formed on a circuit, For example, a microcoil may include a copper coil on a~~
20 ~~printed circuit substrate. The thickness of the card and of the microcoil is of the order of may~~
~~be approximately 1 mm.~~

STRIKETHROUGH SHEET

BRIEF DESCRIPTION OF THE DRAWINGS

Features and advantages of the methods and apparatus of the present invention will be more fully appreciated by reference to the following detailed description of presently preferred but nonetheless illustrative embodiments in accordance with the present invention when taken in conjunction with the accompanying drawings in which:

~~The invention will be better understood on studying the detailed description of some embodiments taken as nonlimiting examples and illustrated by the appended drawings, in which:~~

—figure FIG. 1 depicts ~~is~~ a view of an ~~in~~ axial section of an embodiment of an instrumented antifriction bearing, ~~according to one embodiment of the invention;~~

—figure FIG. 2 depicts ~~is~~ a partial view of the sensor of figure FIG. 1;

—figure FIG. 3 depicts ~~is~~ a frontal view in elevation of the encoder of figure FIG. 1;

—figure FIG. 4 depicts ~~is~~ a frontal view in elevation of an embodiment of an encoder variant;

—figure FIG. 5 depicts ~~is~~ a view ~~in~~ of an axial section of an embodiment of an instrumented antifriction bearing, ~~according to another embodiment of the invention;~~

—figure FIG. 6 depicts ~~is~~ a frontal view in elevation of the encoder of figure FIG. 5; and

—figure FIG. 7 depicts ~~is~~ a wiring diagram of ~~the~~ an embodiment of a sensor.

While the invention is susceptible to various modifications and alternative forms, specific embodiments thereof are shown by way of example in the drawings and will herein be described in detail. It should be understood, however, that the drawings and detailed description thereto are not intended to limit the invention to the particular form disclosed, but

STRIKETHROUGH SHEET

on the contrary, the intention is to cover all modifications, equivalents and alternatives falling within the spirit and scope of the present invention as defined by the appended claims.

STRIKETHROUGH SHEET

DETAILED DESCRIPTION OF EMBODIMENTS

As illustrated in figure FIG. 1, the rolling bearing 1 ~~comprises~~ may include an outer ~~race-track~~ 2; an inner ~~race-track~~ 3; a row of rolling elements 4, ~~here such as~~ balls, placed between the outer ~~race-track~~ 2 and the inner ~~race-track~~ 3 and retained by a cage 5; a seal 6 on one of its sides; ~~and on the opposite side a speed sensor 5 integral-integrated~~ with the outer ~~race-track~~ 2; and an encoder 8 ~~integral-integrated~~ with the inner ~~race-track~~ 3. ~~In the an~~ embodiments shown, the outer ~~race-track~~ is ~~may be~~ nonrotating and the inner ~~race-track~~ is ~~may be~~ rotating. However In an embodiment, the inverse disposition is perfectly conceivable the outer track may be rotating and the inner track may be rotating.

In some embodiments, ~~The~~ a sensor 7 ~~comprises~~ may include a detection portion 9 as depicted in ~~illustrated in~~ greater detail in figure FIG. 2; A sensor may include a support unit made of a ~~in~~ synthetic material; and a metal element 11 fitted onto a bearing surface of the outer ~~race-track~~ 2; ~~here in the A groove in a groove-track usually may be used for to~~ attaching the seal provided in noninstrumented antifriction bearings. A cable 12 may be coupled ~~connected to the detection portion 9 and may be~~ used to transmit information ~~of about~~ speed, ~~of position, and/or or more generally of the~~ rotation parameters. Information may be transmitted to other any units that are capable of exploiting such the data and have not been shown.

In some embodiments, ~~The an~~ encoder 8, ~~see as depicted in figures FIGS. 1 and 3,~~ ~~comprises~~ may include a support portion 13 and an operational portion 14. The support portion 13 ~~is~~ may of tubular in shape. The support portion 13 may be positioned on-fitted onto a cylindrical bearing surface 3a of the inner ~~race-track~~ 3 formed between the ~~race-trackway~~ 3b which is ~~in contact-coupled~~ with the rolling elements 4 and a radial surface 3c which forms the end of the inner ~~race-track~~ 3 in the axial direction on the side of the sensor. The operational portion 14 ~~is~~ may be radial and may include ~~has a~~ plurality of windows 15; of Windows may have a rectangular shape; and may be elongated radially ~~and at the large~~ diameter end of the operational portion 14, allowing a continuous circular portion 16 to remain. The operational portion 14 and the support portion 13 ~~are~~ may be made in a solid unit; and may provideing an economic and particularly robust construction. The encoder 8 may be ~~made from a~~ metal sheet formed by means of pressing and punching steps. It is noticeable

STRIKETHROUGH SHEET

~~that the~~ The operational portion 14 ~~is~~ may be slightly recessed relative to the radial surface 3c of the inner ~~raetrack~~ 3. The encoder 8 ~~is~~ may be therefore particularly compact and ~~is placed~~ positioned in the space defined radially between the ~~raetracks~~ 2 and 3 of the rolling bearing and axially between the rolling elements 4 and the radial plane through which the end surfaces 2c, 3c of said ~~raetracks~~ 2 and 3 pass.

~~_____ In some embodiments, The~~ a detection portion 9 of the sensor 7 ~~comprises~~ may include a support 17, a transmission microcoil 19, and at least four reception microcoils 20. ~~An on which are mounted an integrated circuit 18, for example of the such as an ASIC type, may be mounted on a support 17 and may be used to which is intended for the process data. processing, a~~ A transmission microcoil 19 ~~also called~~ may include an excitation coil, and four reception microcoils 20. The circuit ~~also comprises~~ may include a ~~certain predetermined~~ number of filtering elements such as capacitors, resistors, etc., ~~which are not shown.~~ The detection portion 9 ~~is placed~~ may be positioned axially at a slight distance from the operational portion 14 of the encoder 8 and may occupy ~~occupies~~ an angular sector of the ~~order of approximately 120°; while being inserted into the support unit 10, which for its part is~~ may be substantially circular. ~~If necessary, In an embodiment, a continuous angular sector of 360° could be~~ may be provided for insertion of the detection portion into the support unit. The detection portion 9 ~~has a~~ may include a face, oriented facing the encoder 8, that is not substantially covered by the material of the support unit 10 ~~and oriented facing the encoder 8.~~

~~_____ In some embodiments, The~~ microcoils 19 and 20 ~~are~~ may be of the flat winding types of microcoils. ~~Microcoils and may be of the printed circuits kind or even of the integrated circuits kind.~~ The flatness of the windings may provides the sensor 7 with excellent axial compactness. In addition, the reception coils 20 ~~have~~ may have a square outer contour, ~~and are~~ Reception coils may be positioned ~~placed~~ one after the other on the arc of a circle formed by the support 17, while the transmission coil 19 substantially surrounds the reception coils 20 and is shaped like an arc of a circle. The coils 19 and 20 ~~are connected~~ may be coupled to the data processing circuit 18. ~~The coils 19 and 20 may be, itself connected coupled to to the cable 12 in a manner not shown.~~

~~_____ The~~ A metal element 11 ~~comprises~~ may include a portion that forms ~~forming~~ a hook 11a bent into the a groove of the outer ~~raetrack~~ 2 that may be ~~usually~~ used for fastening a

STRIKETHROUGH SHEET

sealing element which, in a noninstrumented antifriction bearing, ~~is conventionally~~ may be
substantially symmetrical with the seal 6. The metal element 11 ~~is~~ may be supplemented by a
short radial portion directed outward from the portion 11a and an axial portion 11c extending
from the free end of the radial portion 11b. ~~and~~ A short radial portion may be in contact on
one side with the end radial surface 2c of the outer ~~race~~ track 2 and on the other side with the
support unit 10 of the sensor 7, ~~and by an~~ An axial portion 11c extending from the free end
~~of the radial portion 11b may~~ which radially surrounds the support unit 10, with the exception
of the cable outlet zone 12 where ~~provision is made for the support unit 10 to~~ may extend
outward forming a protuberance 21 surrounding the cable 12 and protecting its outlet.

In some embodiments, ~~The~~ a support unit 10 ~~may be~~ is made of a synthetic material
and ~~has~~ may have a generally annular shape with the protuberance 21 projecting over its
periphery, ~~and~~ A support unit may have an axial hollow ~~from on~~ on its radial face on the side of
the antifriction bearing that constitutes a housing for the detection portion 9 while covering it
the detection portion on its face opposite the rolling bearing and over its thickness in the
radial direction. The support unit 10 and the detection portion 9 ~~are integral~~ may be integrated.
As a variant In one embodiment, the support unit 10 could be metallic.

~~Figure FIG. 4 illustrates~~ depicts an embodiment of an encoder variant in which the
support portion 13 is ~~identical~~ similar to that of the preceding embodiment FIG. 3. ~~and~~
~~the~~ The operational portion 14 may be oriented radially outward from the support portion 13.
A support portion may be ~~is~~ formed by a plurality of teeth 22, ~~of generally which may be~~
substantially rectangular in shape, elongated radially, whose periphery is circular, and ~~which~~
~~leave between them~~ crenellations 23 of slightly trapezoidal shape.

~~The mode of operation of the sensor encoder assembly is similar in both embodiments.~~

The reception coils 20 ~~are~~ may be electrically excited by the transmission coil 19 connected
to an oscillating circuit. The transmission coil 19 may generates by induction an electric
signal in the reception coils 20. During the rotation of the encoder 8, the windows and the
full portions of the operational portion 14 passing before the microcoils may produces a
variation of the metal mass situated in front of each reception microcoil 20. ~~In said the~~
reception coils 20, this may results in a variation of the phase of the electric signal induced

STRIKETHROUGH SHEET

due to losses by eddy currents. These variations of the electric signal emitted by the various reception coils 20 and processed by the circuit 18 ~~are~~ may be the basis of the generation of signals representative of the parameters of rotation of the encoder 8, such as the speed of rotation.

5

In some embodiments, ~~The~~ a sensor with microcoils may allows the instrumented antifriction bearing to deliver reliable information, ~~including even~~ when magnetic fields of high intensity are present. The encoder may be made of an electrically conducting and magnetic metal material, such as steel, or ~~yet~~ electrically conducting and nonmagnetic material, such as aluminum or copper.

10

~~The~~ Reception microcoils 20 may operate in pairs to deliver a differential signal. The reception microcoils 20 of a pair may be angularly offset by an angle represented by β , ~~and the~~ An angular pitch of the windows is represented by ϕ . For the signal to be out of phase, ~~requires that~~ one of these angles may ~~should~~ not be a multiple of the other. This therefore gives $\beta \neq a \cdot \phi$ where a is any integer, the angle β usually being greater than ϕ . For example this could be $\beta = (a+0.5) \cdot \phi$ or $\beta = (a+0.25) \cdot \phi$.

15

~~When the~~ an encoder passes in rotation before the sensor, the discontinuities of material of the operational portion 14 may cause periodic variations of the metal mass that is opposite the reception microcoils 20. If there is metal material before each of the coils of a pair of reception coils, the phase difference between the two differential coils ~~is~~ may be zero. If there is metal material before at least one of the two reception coils forming a pair and the metal material is distributed differently before each coil, the losses due to the eddy currents in the metal material ~~will~~ may generate a phase difference of the currents. This phase difference may then be processed and extracted adequately by the processing circuit 18, in order to obtain ~~the~~ desired information, such as ~~the~~ angular speed, ~~the~~ direction of rotation, ~~the~~ position, etc.

20

25

In some embodiments, ~~The~~ generation of ~~the~~ an electronic signal ~~does~~ may not ~~therefore~~ depend on the level or the direction of a magnetic field sensed by the microcoils, but on the modification of the currents induced by the excitation coil 19 in the reception coils 20 in the presence of the variations of the electrically conducting metal masses passing before

30

STRIKETHROUGH SHEET

said microcoils. The signal ~~is~~ may be therefore very insensitive to external magnetic fields, which makes the device according to the invention extremely suitable for operating in an environment subjected to strong magnetic fields such as electric motors. The reception coils 20 ~~are~~ may be distributed on the support 17 with a radial position and angular pitch suitable for cooperating with the operational portion 14 of the encoder 8 and/or delivering the required signals. ~~If necessary,~~ In an embodiment, the number of reception coils 20 may be increased in the circumferential direction and/or stacking of several coils may be stacked in the axial direction ~~may be used in order to obtain higher powered signals.~~

In some embodiments, ~~Since the microcoils and/or processing circuit 18 are~~ may be extremely thin, ~~as is the processing circuit 18,~~ the sensor 7 ~~has~~ may have extremely small axial dimensions, which may allowing integration into a sensor unit 10 ~~itself having very small axial dimensions.~~ Likewise, the encoder ~~may be,~~ due to its structure, ~~be axially extremely thin axially and may be easily integrated into the space lying between the bearing racetracks,~~ such that ~~said the~~ encoder does not affect the external dimensions of the instrumented antifriction bearing.

~~FIGS. Figures 5 and 6 show depict and embodiment of a variant with an encoder 8 made with the a printed circuit technique.~~ From a conventional printed circuit substrate coated with a thin metal layer, such as copper ~~for example,~~ a disk ~~is made~~ may be made including comprising an alternation of metallized sectors 8a and of nonmetallized sectors 8b. The substrate ~~is~~ may be electrically nonconducting and the metallized sectors 8a ~~are~~ may be electrically conducting.

~~This A disk is~~ may be coupled attached by appropriate means (e.g., by appropriate means, such as fitment and/or bonding) onto an axial portion 3d ~~made for this purpose on the rotating racetrack 3 of the bearing 1. The axial portion 3d may be configured to be coupled to the disk.~~ This type of encoder wheel has little inertia, great axial compactness, and the contours of the active portions may be made with great precision. The aggregate signal ~~is may be therefore particularly weak.~~

~~Figure FIG. 7 illustrates depicts in greater detail the electrical functions of the an embodiment of the system. It shows that the r~~Reception coils 20 ~~are~~ may be grouped in two

STRIKETHROUGH SHEET

pairs numbered 24 and 25 and framed by dashed lines. For clarity of the drawing, the pairs of reception coils 24 and 25 are shown outside the exciting transmission coil whereas in reality they are inside said transmission coil 19. The coils 19 and 20 are connected may be coupled to the processing circuit 18. The processing circuit 18 ~~comprises~~ may include an oscillator 26, whose output is connected to the transmission coil 19, and two phase demodulators 27 and 28 ~~connected~~ coupled to the output of each of the reception coils 20. In an embodiment, the circuit 18 ~~also comprises~~ may include two interpolating comparators 29, 30, ~~mounted~~ positioned ~~respectively~~ at the output of the phase demodulators 27 and 28. At the output, the processing circuit 18 may transmits a digital signal representative of at least one parameter of rotation of the antifriction bearing, such as ~~the speed, the position, the direction of rotation,~~ ~~the acceleration,~~ etc.

In some embodiments, This is the method of producing an instrumented antifriction bearing may be produced that can be easily integrated into a mechanical assembly due to its small bulk. ~~The instrumented antifriction bearing may is capable of operating~~ at high temperatures, such as those existing in an electric motor, and/or ~~capable of operating~~ in an environment subjected to strong magnetic fields. Through these qualities, the instrumented antifriction bearing according to the invention has worthwhile capabilities for use in a high power asynchronous electric motor, the ~~The instrumented antifriction bearing being able to~~ may fulfill both the mechanical function of a bearing and the electronic functions of detection necessary to control the motor.

In this patent, certain U.S. patents, U.S. patent applications, and other materials (e.g., articles) have been incorporated by reference. The text of such U.S. patents, U.S. patent applications, and other materials is, however, only incorporated by reference to the extent that no conflict exists between such text and the other statements and drawings set forth herein. In the event of such conflict, then any such conflicting text in such incorporated by reference U.S. patents, U.S. patent applications, and other materials is specifically not incorporated by reference in this patent.

Further modifications and alternative embodiments of various aspects of the invention will be apparent to those skilled in the art in view of this description. Accordingly, this description is to be construed as illustrative only and is for the purpose of teaching those

STRIKETHROUGH SHEET

5 skilled in the art the general manner of carrying out the invention. It is to be understood that
the forms of the invention shown and described herein are to be taken as the presently
preferred embodiments. Elements and materials may be substituted for those illustrated and
described herein, parts and processes may be reversed, and certain features of the invention
may be utilized independently, all as would be apparent to one skilled in the art after having
the benefit of this description of the invention. Changes may be made in the elements
described herein without departing from the spirit and scope of the invention as described in
the following claims.

10

STRIKETHROUGH SHEET

ABSTRACT

~~The invention concerns an~~An instrumented ball-bearing may include, comprising a rotating part, a non-rotating part, and an assembly for detecting rotation parameters. The assembly for detecting rotation parameters may include including an encoder (8) and a sensor (7). The sensor may be integrated integral with said the non-rotating part, and The sensor may include provided with a sensor unit (10), and with at least a microcoil. The microcoil may have having a substantially planar winding. The microcoil may be positioned arranged in the sensor unit (10) of the non-rotating part such that the microcoil is urged to may be positioned axially opposite the encoder (8).